



Distribuido Por:

Eastman IMPEX

2018



SUNWIDE

Distributed By:

Eastman IMPEX

ROLIT6

PERFORMANCE DESIGN FOR ALL SEASON



Wide center rib reinforces tread, provides excellent lateral stability.

4 main groove design shows excellent control and traction.

The whole rib designed tread reduces rolling resistance, more economic.

Block design on shoulder provides stable steering control.

Small shoulder rib design can avoid irregular treadwear, reduce noise.



NO	SIZE	L/I&SS	UTQG	OD (mm)	SW (mm)	RIM	G.D				dB	
1	155/65R13	73T	M+S	400AA	532	157	4.5J	7.6	F	B		70
2	155/70R13	75T	M+S	400AA	548	157	4.5J	7.6	F	B		70
3	155/80R13	79T	M+S	400AA	578	157	4.5J	7.6	F	B		70
4	165/65R13	77T	M+S	400AA	578	157	4.5J	7.6	F	B		70
5	165/70R13	79T	M+S	400AA	562	170	5.0J	7.6	F	B		70
6	165/80R13	83T	M+S	400AA	594	165	4.5J	7.6	F	B		70
7	175/60R13	77T	M+S	400AA	540	177	5.0J	7.6	F	B		70
8	175/70R13	82T	M+S	400AA	576	177	5.0J	7.8	F	B		70
9	185/70R13	86T	M+S	400AA	590	189	5.5J	7.8	F	B		70
10	185/70R13	86H	M+S	400AA	590	189	5.5J	7.8	F	B		70
11	165/70R14	81T	M+S	400AA	588	170	5.0J	7.6	F	B		70
12	175/65R14	82H	M+S	400AA	584	177	5.0J	7.6	F	B		70
13	175/65R14	82T	M+S	400AA	584	177	5.0J	7.6	F	B		70
14	175/65R14	86TXL	M+S	400AA	584	177	5.0J	7.6	F	B		70
15	175/70R14	84T	M+S	400AA	602	177	5.0J	7.6	F	B		70
16	185/60R14	82H	M+S	400AA	578	189	5.5J	7.8	F	B		70
17	185/65R14	86H	M+S	400AA	596	189	5.5J	7.8	F	B		70
18	185/70R14	88H	M+S	400AA	616	189	5.5J	8.0	F	B		70
19	195/60R14	86H	M+S	400AA	590	201	6.0J	7.8	F	B		70
20	195/65R14	89H	M+S	400AA	610	201	6.0J	8.0	F	B		70
21	195/70R14	91H	M+S	400AA	630	201	6.0J	8.0	E	B		70
22	205/60R14	88H	M+S	400AA	602	209	6.0J	8.0	F	B		70
23	205/70R14	95H	M+S	400AA	644	209	6.0J	8.2	E	B		70
24	215/70R14	96H	M+S	400AA	658	221	6.5J	8.2	E	B		70
25	185/55R15	82H	M+S	400AA	585	194	6.0J	8.0	F	B		70
26	185/55R15	82V	M+S	400AA	585	194	6.0J	8.0	F	B		70
27	185/60R15	88H XL	M+S	400AA	603	189	5.5J	8.0	F	B		70
28	185/65R15	88H	M+S	400AA	621	189	5.5J	8.0	F	B		70
29	195/50R15	82H	M+S	400AA	577	201	6.0J	8.0	F	B		70

➔ NEXT PAGE

NO	SIZE	L/ISS	UTQG	OD (mm)	SW (mm)	RIM	G.D					dB
30	195/55R15	85V	M+S 400AA	595	201	6.0J	8.0	F	B			70
31	195/60R15	88H	M+S 400AA	615	201	6.0J	8.0	F	B			70
32	195/65R15	91H	M+S 400AA	635	201	6.0J	7.6	E	B			70
33	195/65R15	91V	M+S 400AA	635	201	6.0J	7.6	E	B			70
34	205/60R15	91H	M+S 400AA	627	209	6.0J	8.0	E	B			70
35	205/65R15	94H	M+S 400AA	647	209	6.0J	8.2	E	B			70
36	205/65R15	94V	M+S 400AA	647	209	6.0J	8.2	E	B			70
37	205/70R15	96H	M+S 400AA	669	209	6.0J	8.2	E	B			70
38	215/60R15	94H	M+S 400AA	639	221	6.5J	8.2	E	B			70
39	215/65R15	96H	M+S 400AA	661	221	6.5J	8.2	E	B			70
40	215/70R15	98H	M+S 400AA	683	221	6.5J	8.2	E	B			70
41	225/60R15	96V	M+S 400AA	651	228	6.5J	8.2	E	B			70
42	195/55R16	91V XL	M+S 400AA	620	201	6.0J	8.2	E	B			70
43	195/60R16	89H	M+S 400AA	640	201	6.0J	8.2	E	B			70
44	205/55R16	94V XL	M+S 400AA	632	214	6.5J	8.2	E	B			70
45	205/60R16	92H	M+S 400AA	652	209	6.0J	8.2	E	B			70
46	205/65R16	95H	M+S 400AA	672	209	6.0J	8.2	E	B			70
47	215/55R16	93V	M+S 400AA	342	226	7.0J	8.2	E	B			70
48	215/55R16	97W	M+S 400AA	342	226	7.0J	8.2	E	B			70
49	215/60R16	95H	M+S 400AA	664	221	6.5J	8.2	E	B			70
50	215/65R16	98H	M+S 400AA	686	221	6.5J	8.2	E	B			70
51	225/55R16	95V	M+S 400AA	654	233	7.0J	8.2	E	B			70
52	225/60R16	98H	M+S 400AA	676	228	6.5J	8.2	E	B			70
53	235/60 R16	100H	M+S 400AA	688	240	7.0J	8.2	E	B			70
54	215/55R17	94V	M+S 400AA	668	226	7.0J	8.2	E	B			70
55	225/55R17	101H XL	M+S 400AA	680	233	7.0J	8.2	E	B			70



ROLIT6

ROLIT9



NO	SIZE	L/ISS	UTQG	OD (mm)	SW (mm)	RIM	G.D
1	195/65R15	91H	M+S 460AA	635	201	6.0J	8.2
2	215/60 R15	94H	M+S 460AA	639	218	6.5J	8.5
3	215/75R15	100H	M+S 460AA	703	216	6.0J	8.5
4	205/50R16	87V/W	M+S 460AA	612	214	6.5J	8.2
5	225/55R16	99V XL	M+S 460AA	654	233	7.0J	8.5
6	235/60 R16	100H/V	M+S 460AA	688	240	7.0J	8.5
7	225/55 R18	98V	M+S 460AA	705	233	7.0J	8.5

PCR

UHP

HT

AT

MT

LTR

WINTER

RS-zero



- Newly Balanced Performance**
 -Brilliant wet-grip performance for greater safety and low rolling resistance for fuel efficiency
- Wide Lateral Grooves**
 -For better aquaplaning performance
- Closed & Notched Shoulder**
 -Excellent handling and cornering in dry and wet conditions
 -3 wide channels for better drainage



NO	SIZE	L/ISS	UTQG	OD (mm)	SW (mm)	RIM	G.D				dB
1	155/70R13	75T	360AA	548	157	4.5J	7.2	E	B		69
2	165/65R13	77H	360AA	544	170	5.0B	7.5	E	B		69
3	165/70R13	79T	360AA	562	170	5.0J	7.2	E	B		69
4	*165/80R13	83T	360AA	594	165	4.5J	7.2	E	B		69
5	175/70R13	82T	360AA	576	177	5.0J	7.2	E	B		69
6	*185/70R13	86H	360AA	590	189	5.5J	7.2	E	B		69
7	155/65R14	75T	360AA	558	157	4.5J	7.2	E	B		69
8	*155/70R14	77T	360AA	574	157	4.5J	7.2	E	B		69
9	165/60R14	75H	400AA	554	170	5.0J	7.5	E	B		69
10	165/65R14	79T	400AA	570	170	5.0J	7.5	E	B		69
11	165/70R14	81T	360AA	588	170	5.0J	7.2	E	B		69
12	175/65R14	82T	400AA	584	177	5.0J	7.5	E	B		69
13	175/65R14	82H	400AA	584	177	5.0J	7.5	E	B		69
14	175/65R14	86T XL	400AA	584	177	5.0J	7.5	E	B		69
15	175/70R14	84H	360AA	602	177	5.0J	7.2	C	B		69
16	185/60R14	82H	400AA	578	189	5.5J	7.5	E	B		69
17	185/65R14	86H	400AA	596	189	5.5J	7.5	C	B		69
18	185/70R14	88H	400AA	616	189	5.5J	7.2	C	B		69
19	195/60R14	86H	400AA	590	201	6.0J	7.5	C	B		69
20	195/70R14	91H	400AA	630	201	6.0J	7.5	C	B		69
21	175/60R15	81H	360AA	591	177	5.0J	7.5	E	B		69
22	175/65R15	84H	360AA	609	177	5.0J	7.5	C	B		69
23	185/55R15	82H	400AA	585	194	6.0J	7.5	E	B		69
24	185/55R15	82V	400AA	585	194	6.0J	7.5	E	B		69
25	185/60R15	84H	400AA	603	189	5.5J	7.5	C	B		69
26	185/60R15	88H XL	400AA	603	189	5.5J	7.5	C	B		69
27	185/65R15	88T	400AA	621	189	5.5J	7.5	C	B		69
28	185/65R15	88H	400AA	621	189	5.5J	7.5	C	B		69
29	195/60R15	88H	400AA	615	201	6.0J	7.5	C	B		69
30	195/60R15	88V	400AA	615	201	6.0J	7.5	C	B		69
31	195/65R15	91H	400AA	635	201	6.0J	7.5	C	B		69
32	195/65R15	91V	400AA	635	201	6.0J	7.5	C	B		69
33	195/65R15	95T XL	400AA	635	201	6.0J	7.5	C	B		69

RS-one



NO	SIZE	LI&SS	UTQG	OD (mm)	SW (mm)	RIM	G.D				dB
1	195/50R15	82V	400AA	577	201	6.0J	7.8	C	B		69
2	195/55R15	85V	400AA	595	201	6.0J	7.8	C	B		69
3	205/60R15	91H	400AA	627	209	6.0J	7.8	C	B		69
4	205/60R15	91V	400AA	627	209	6.0J	7.8	C	B		69
5	205/65R15	94H	400AA	647	209	6.0J	7.8	C	B		69
6	205/65R15	94V	400AA	647	209	6.0J	7.8	C	B		69
7	205/70R15	96H	400AA	669	209	6.0J	7.8	C	B		69
8	195/45R18	84V	400AA	582	195	6.5J	7.8	C	B		69
9	195/50R16	84V	400AA	602	201	6.0J	7.8	C	B		69
10	195/55R16	91W	400AA	620	201	6.0J	7.8	C	B		69
11	205/45R16	87V XL	320AA	590	206	7.0J	7.8	C	B		69
12	205/45ZR16	87W XL	320AA	590	206	7.0J	7.8	C	B		69
13	205/50ZR16	87W	320AA	612	214	6.5J	7.8	C	B		69
14	205/55R16	91V	320AA	632	214	6.5J	7.8	C	B		69
15	205/55ZR16	91W	320AA	632	214	6.5J	7.8	C	B		69
16	205/55R16	94V XL	320AA	632	214	6.5J	7.8	C	B		69
17	205/55ZR16	94W XL	320AA	632	214	6.5J	7.8	C	B		69
18	205/60R16	92H	400AA	652	209	6.0J	7.8	C	B		69
19	205/60R16	92V	400AA	652	209	6.0J	7.8	C	B		69
20	205/65R16	95H	400AA	672	209	6.0J	7.8	C	B		69
21	215/55ZR16	97W XL	320AA	642	226	7.0J	7.8	C	B		69
22	215/60R16	95V	400AA	664	221	6.5J	7.8	C	B		69
23	215/60R16	99H XL	400AA	664	221	6.5J	7.8	C	B		69
24	215/60R16	99V XL	400AA	664	221	6.5J	7.8	C	B		69
25	*215/65R16	98H	400AA	686	221	6.5J	7.8	C	B		69
26	225/50R16	92V	320AA	632	233	7.0J	7.8	C	B		69
27	225/50R16	96W XL	320AA	632	233	7.0J	7.8	C	B		69
28	225/55R16	99V XL	320AA	654	233	7.0J	7.8	C	B		69
29	225/55ZR16	99W XL	320AA	654	233	7.0J	7.8	C	B		69
30	205/40ZR17	84W XL	320AA	596	212	7.5J	7.8	C	B		69
31	205/45ZR17	88W XL	320AA	616	206	7.0J	7.8	C	B		69
32	205/50R17	89V	320AA	638	214	6.5J	7.8	C	B		69
33	205/50ZR17	93W XL	320AA	638	214	6.5J	7.8	C	B		69
34	215/40ZR17	87W XL	320AA	604	218	7.5J	7.8	C	B		69
35	215/45ZR17	91W XL	320AA	626	213	7.0J	7.8	C	B		69
36	215/50R17	91V	320AA	648	226	7.0J	7.8	C	B		69
37	215/50ZR17	95W XL	320AA	648	226	7.0J	7.8	C	B		69
38	215/55ZR17	98W XL	320AA	668	226	7.0J	7.8	C	B		69
39	225/45ZR17	94W XL	320AA	634	225	7.5J	7.8	C	B		69
40	225/50R17	94V	320AA	658	233	7.0J	7.8	C	B		69
41	225/50ZR17	98W XL	320AA	658	233	7.0J	7.8	C	B		69
42	225/55R17	97V	320AA	680	233	7.0J	7.8	C	B		69
43	225/55ZR17	97W	320AA	680	233	7.0J	7.8	C	B		69

➔ NEXT PAGE

PCR

UHP

HT

AT

MT

LTR

WINTER

● **Solid Rib-Type Design**

-Improved wet braking and reinforced block stiffness by centralized ribbed-pattern design

● **Wide Lateral Grooves**

-Wide lateral grooves help to maximize water displacement when turning

● **Wide 4 Channels Main Grooves**

-The pattern design with its 4 wide linear grooves improves water displacement performance



NO	SIZE	L/ISS	UTQG	OD (mm)	SW (mm)	RIM	G.D					dB
44	225/55ZR17	101W XL	320AA	680	233	7.0J	7.8	C	B			69
45	235/55R17	103V XL	320AA	690	245	7.5J	7.8	C	B			69
46	235/45ZR17	97W XL	320AA	644	236	8.0J	7.8	C	B			69
47	235/50ZR17	100W XL	320AA	668	245	7.5J	7.8	C	B			69
48	245/40ZR17	95W XL	320AA	628	248	8.5J	7.8	C	B			69
49	245/45ZR17	99W XL	320AA	652	243	8.0J	7.8	C	B			69
50	215/35ZR18	84W XL	320AA	607	218	7.5J	7.8	C	B			69
51	215/40ZR18	89W XL	320AA	629	218	7.5J	7.8	C	B			69
52	215/45ZR18	93W XL	320AA	651	213	7.0J	7.8	C	B			69
53	225/40ZR18	92W XL	320AA	637	230	8.0J	7.8	C	B			69
54	225/45ZR18	95W XL	320AA	659	225	7.5J	7.8	C	B			69
55	235/40ZR18	96W XL	320AA	645	241	8.5J	7.8	C	B			69
56	235/45ZR18	100W XL	320AA	669	236	8.0J	7.8	C	B			69
57	245/40ZR18	97W XL	320AA	653	248	8.5J	7.8	C	B			69
58	245/45ZR18	100W XL	320AA	677	243	8.0J	7.8	C	B			69
59	245/50ZR18	104W XL	320AA	703	253	7.5J	7.8	C	B			69
60	255/35ZR18	94W XL	320AA	635	260	9.0J	7.8	C	B			69
61	255/45ZR18	103W XL	320AA	687	255	8.5J	7.8	C	B			69
62	255/55ZR18	109W XL	320AA	737	265	8.0J	7.8	C	B			69
63	225/35ZR19	88W XL	320AA	641	230	8.0J	7.8	C	B			69
64	235/35ZR19	91W XL	320AA	647	241	8.5J	7.8	C	B			69
65	245/35ZR19	93W XL	320AA	655	248	8.5J	7.8	C	B			69
66	245/45ZR19	102W XL	320AA	703	243	8.0J	7.8	C	B			69
67	255/30ZR19	91W XL	320AA	637	260	9.0J	7.8	C	B			69
68	255/35ZR19	96W XL	320AA	661	260	9.0J	7.8	C	B			69
69	255/40ZR19	100W XL	320AA	687	260	9.0J	7.8	C	B			69
70	255/30ZR20	92W XL	320AA	662	260	9.0J	7.5	C	B			69
71	275/35ZR20	102W XL	320AA	700	278	9.5J	7.5	C	B			69
72	295/40ZR22	112W XL	320AA	795	301	10.5J	7.5	C	B			69

REXTON-1

DRY PERFORMANCE

WET PERFORMANCE

RIDE COMFORT

QUIETNESS



NO	SIZE	L/ISS	OD (mm)	SW (mm)	RIM	G.D
1	225/30R20	85WXL	644	230	8.0J	7.9
2	225/35R20	90WXL	666	230	8.0J	7.9
3	245/35R20	95W XL	680	248	8.5J	7.9
4	255/35R20	97WXL	686	260	9.0J	7.9
5	275/40R20	106V XL	728	278	9.5J	7.9
6	275/45R20	110H/V XL	756	273	9.0J	7.9
7	285/50R20	116H/V XL	794	297	9.0J	7.9
8	245/30R22	92W XL	707	248	8.5J	7.9
9	255/30R22	95W XL	713	260	9.0J	7.9
10	265/35R22	102V XL	745	271	9.5J	7.9
11	305/40R22	114V XL	803	313	11.0J	7.9
12	255/30R24	97V XL	764	260	9.0J	7.9
13	305/35R24	112V XL	824	313	11.0J	7.9

TRAVOMAX

UTQG 700AA



Four wide longitudinal grooves ensure high efficient water evacuation and optimized grooves width prevent tire lateral slide

Special tread compound with optimized rubber filler can balance tire tread wear and traction performance



3D zigzag Winter sipes can help maintain block rigidity by locking together and enhance wet/snow performance

Strong block bridge, can avoid Heel-Toe irregular treadwear, improve treadwear resistance.

Continuous 3 center ribs help directional driving stability at high speed

NO	SIZE	L/ISS	UTQG	OD (mm)	SW (mm)	RIM	G.D
1	P205/55R16	89H/V	M+S	700AA	632	214	6.5J 8.7
2	P215/55R16	91H/V	M+S	700AA	642	226	7.0J 8.7
3	P215/60R16	94H/V	M+S	700AA	664	221	6.5J 8.7
4	P225/55R16	94H/V	M+S	700AA	654	233	7.0J 8.7
5	P225/60R16	97H/V	M+S	700AA	676	228	6.5J 8.7
6	P215/55R17	93H/V	M+S	700AA	668	226	7.0J 8.7
7	P215/60R17	95H/V	M+S	700AA	690	221	6.5J 8.7
8	P215/65R17	98H/V	M+S	700AA	712	221	6.5J 8.7
9	P225/55R17	95H/V	M+S	700AA	680	233	7.0J 8.7
10	P225/60R17	98H/V	M+S	700AA	702	228	6.5J 8.7
11	P225/55R18	97H/V	M+S	700AA	705	233	7.0J 8.7
12	P225/60R18	99H/V	M+S	700AA	727	228	6.5J 8.7

ECOROAD



Optimal design of pattern order with 5 changing pitches, can avoid irregular tread wear, reduce noise. Assure tire U/F & Balance ability.

Lots of small transverse pattern design assure good performance after treadwear, and decrease noise.

Dynamic shoulder decoration design, can discharge heat from belt efficiently, improve driving security.



Small pattern design on winter tire can enhance braking ability on dry wet road and snow road, assure good all-season capacity.

The Tie-Bar on shoulder, can decrease noise & block deformation, improve treadwear capacity.

Strong block bridge, can avoid Heel-Toe irregular treadwear, improve treadwear resistance.

NO	SIZE	L/ISS	UTQG	OD (mm)	SW (mm)	RIM	G.D
1	175/65R14	82T	M+S	480AA	584	177	5.0J 7.8
2	185/60R14	82H	M+S	480AA	578	189	5.5J 7.8
3	185/65R14	86H/T	M+S	480AA	596	187	5.5J 7.8
4	185/70R14	88T	M+S	480AA	616	187	5.5J 7.8
5	195/60R14	86H	M+S	480AA	590	201	6.0J 8.1
6	195/70R14	91T	M+S	480AA	630	198	6.0J 7.8
7	205/70R14	95T	M+S	480AA	644	208	6.0J 8.1
8	215/70R14	96T	M+S	480AA	658	221	6.5J 8.1
9	185/55R15	82H/V	M+S	480AA	585	194	6.0J 7.8
10	185/60R15	84T/H	M+S	480AA	603	189	5.5J 7.8
11	185/65R15	88T/H	M+S	480AA	621	189	5.5J 7.8
12	195/55R15	85H/V	M+S	480AA	595	201	6.0J 8.1
13	195/60R15	88H/V	M+S	480AA	615	198	6.0J 8.1
14	195/65R15	91H/V/T	M+S	480AA	635	201	6.0J 8.1
15	205/60R15	91H/V	M+S	480AA	627	210	6.0J 8.1
16	205/65R15	94H/V	M+S	480AA	647	209	6.0J 8.1
17	205/70R15	96T	M+S	480AA	669	206	6.0J 8.1
18	215/65R15	96H/V	M+S	480AA	661	221	6.5J 8.1
19	215/70R15	98T	M+S	480AA	684	219	6.5J 8.1
20	205/55R16	91H/V	M+S	480AA	632	214	6.5J 8.1
21	205/60R16	92H/V	M+S	480AA	652	209	6.0J 8.1
22	205/65R16	95H/V	M+S	480AA	672	209	6.0J 8.1
23	215/55R16	93H/V	M+S	480AA	642	226	7.0J 8.1
24	215/60R16	95H/V	M+S	480AA	664	221	6.5J 8.1
25	215/65R16	98T/H/V	M+S	480AA	686	221	6.5J 8.1
26	225/60R16	98H/V	M+S	480AA	676	228	6.5J 8.1
27	P175/70R13	82S/T	M+S	480AA	576	177	5.0J 7.8
28	P205/75R14	95S/T	M+S	480AA	664	203	5.5J 8.1
29	P195/75R14	92S/T	M+S	480AA	648	196	5.5J 7.8
30	P155/80R13	79T	M+S	480AA	578	157	4.5J 7.6
31	P185/75R14	89S/T	M+S	480AA	634	184	5.0J 7.8
32	165/80R15	87T	M+S	480AA	645	165	4.5J 7.6
33	P215/75R14	98S/T	M+S	480AA	678	216	6.0J 8.1
34	P175/70R14	84S/T	M+S	480AA	602	177	5.0J 7.8

CONQUEST



NO	SIZE	LI&SS	OD (mm)	SW (mm)	RIM	G.D
1	215/65R16	98H	686	221	6.5J	8.0
2	215/70R16	100H	708	221	6.5J	8.0
3	225/70R16	103H	722	228	6.5J	8.0
4	235/70R16	106H	736	240	7.0J	8.0
5	245/70R16	111H XL	750	248	7.0J	8.0
6	265/70R16	112H	778	272	8.0J	8.0
7	215/60R17	96V	690	221	6.5J	8.0
8	225/60R17	99H	702	228	6.5J	8.0
9	225/65R17	102H	724	228	6.5J	8.0
10	235/60R17	102H	714	240	7.0J	8.0
11	235/55R17	99/103V XL	690	245	7.5J	8.0
12	235/65R17	104/108H XL	738	240	7.0J	8.0
13	245/65R17	111H XL	750	248	7.0J	8.0
14	265/65R17	112H	776	272	8.0J	8.0
15	215/55R18	95V	693	226	7.0J	8.0
16	235/50R18	101V XL	693	245	7.5J	8.0
17	235/55R18	104V XL	715	245	7.5J	8.0
18	235/60R18	107V XL	739	240	7.0J	8.0
19	255/55R18	109V XL	737	265	8.0J	8.0
20	285/60R18	116V	799	292	8.5J	8.0
21	255/55R19	111V XL	763	265	8.0J	8.0

PCR

UHP

HT

AT

MT

LTR

WINTER

DUREVER



- 4 Longitudinal main grooves contribute to the efficient drainage of water which provides excellent driving stability on wet roads.
- All season pattern design provides comfortable & silent driving pleasure.
- Wide center rib and tread design provides excellent lateral stability, and assures superior tread wear performance.

NO	SIZE	L/I&SS		OD (mm)	SW (mm)	RIM	G.D
1	205/70R15	96H	M+S	669	209	6.0J	8.2
2	235/75R15	105H	M+S	733	235	6.5J	9.0
3	215/65R16	102H XL	M+S	686	221	6.5J	8.2
4	235/60R16	100H	M+S	688	240	7.0J	9.0
5	225/70R16	103H	M+S	722	228	6.5J	9.0
6	235/70R16	106H	M+S	736	240	7.0J	9.2
7	245/70R16	107H	M+S	750	248	7.0J	9.2
8	265/70R16	112H	M+S	778	272	8.0J	9.5
9	225/65R17	102H XL	M+S	724	228	6.5J	8.3
10	235/65R17	108V XL	M+S	738	240	7.0J	9.0
11	235/60R18	107V XL	M+S	739	240	7.0J	9.0
12	255/55R18	109V XL	M+S	737	265	8.0J	9.0



DUREVOLE AT



NO	SIZE	L/ISS	PR	UTQG	OD (mm)	SW (mm)	RIM	G.D
1	235/75R15	109T XL	M+S	480AB	733	235	6.5J	9.5
2	215/70R16	100T	M+S	480AB	708	221	6.5J	9.5
3	235/70R16	106T	M+S	480AB	736	240	7.0J	9.5
4	245/70R16	107T	M+S	480AB	750	248	7.0J	9.5
5	265/70R16	112T	M+S	480AB	778	272	8.0J	9.5
6	275/70R16	114T	M+S	480AB	792	279	8.0J	9.5
7	225/65R17	102T	M+S	480AB	724	228	6.5J	9.5
8	235/65R17	108T XL	M+S	480AB	738	240	7.0J	9.5
9	245/65R17	107T	M+S	480AB	750	248	7.0J	9.5
10	265/65R17	112T	M+S	480AB	776	272	8.0J	9.5
11	265/70R17	115T	M+S	480AB	804	272	8.0J	9.5
12	265/60R18	110T	M+S	480AB	775	272	8.0J	9.5
13	275/65R18	116T	M+S	480AB	815	279	8.0J	9.5
14	285/60R18	116T	M+S	480AB	799	292	8.5J	9.5
15	265/50R20	111T XL	M+S	480AB	774	277	8.5J	9.5
16	275/55R20	117T XL	M+S	480AB	810	284	8.5J	9.5
17	275/60R20	115T	M+S	480AB	838	279	8.0J	9.5
18	LT31*10.5R15	109S	6	M+S	769	275	8.5J	11.5
19	LT215/75R15	106/103S	8	M+S	703	216	6.0J	11.5
20	LT215/85R16	115/112S	10	M+S	772	216	6.0J	11.5
21	LT225/75R16	115/112S	10	M+S	744	223	6.0J	11.5
22	LT235/85R16	120/116S	10	M+S	806	235	6.5J	11.5
23	LT245/75R16	120/116S	10	M+S	777	250	7.0J	11.5
24	LT265/75R16	123/120S	10	M+S	807	270	7.5J	11.5
25	LT285/75R16	122/119S	8	M+S	834	286	8.0J	11.5
26	LT265/70R17	121/118S	10	M+S	804	272	8.0J	11.5
27	LT285/70R17	121/118S	8	M+S	832	292	8.5J	11.5
28	LT275/65R20	126/123S	10	M+S	866	279	8.0J	11.5

HUNTSMAN

FACE THE NEXT CHALLENGE..

DRY PERFORMANCE

WET PERFORMANCE

RIDE COMFORT

OFF ROAD PERFORMANCE



NO	SIZE	L/ISS	PR	OD (mm)	SW (mm)	RIM	G.D (1/32")
1	27*8.50R14LT	95Q	6	674	218	7.0J	14.3
2	31*10.50R15LT	109Q	6	775	268	8.5J	14.7
3	32*11.50R15LT	113Q	6	801	290	9.0J	14.3
4	33*12.50R15LT	108Q	6	826	318	10.0J	15.1
5	33*12.50R17LT	114Q	8	826	318	10.0J	15.1
6	35*12.50R17LT	121Q	10	877	318	10.0J	14.3
7	33*12.50R18LT	118Q	10	826	318	10.0J	15.1
8	35*12.50R18LT	123Q	10	877	318	10.0J	14.3
9	33*12.50R20LT	114Q	10	826	318	10.0J	14.3
10	35*12.50R20LT	121Q	10	877	318	10.0J	14.3
11	37*13.50R20LT	127Q	10	928	345	11.0J	14.9
12	33*12.50R22LT	109Q	10	826	318	10.0J	14.3
13	35*12.50R22LT	127Q	10	877	318	10.0J	14.3
14	37*13.50R22LT	123Q	10	928	345	11.0J	14.9
15	LT215/75R15	106/103Q	8	703	216	6.0J	14.3
16	LT235/75R15	104/101Q	6	733	235	6.5J	14.3
17	LT225/75R16	115/112Q	10	744	223	6.0J	14.3
18	LT235/70R16	110/107Q	8	736	240	7.0J	14.3
19	LT235/85R16	120/116Q	10	806	235	6.5J	14.3
20	LT245/70R16	113/110Q	8	750	248	7.0J	14.3
21	LT245/75R16	120/116Q	10	774	248	7.0J	14.3
22	LT265/75R16	123/120Q	10	804	267	7.5J	14.7
23	LT285/75R16	122/119Q	8	834	286	8.0J	14.9
24	LT285/75R16	128/123Q	10	834	286	8.0J	14.9
25	LT265/65R17	120/117Q	10	776	272	8.0J	14.3
26	LT265/70R17	118/115Q	8	804	272	8.0J	14.7
27	LT285/70R17	121/118Q	10	832	292	8.5J	14.9
28	31*10.5R15LT <small>RWL</small>	109Q	6	775	268	8.5J	14.7
29	33*12.5R15LT <small>RWL</small>	108Q	6	826	318	10.0J	15.1
30	LT215/75R15 <small>RWL</small>	106/103Q	8	703	216	6.0J	14.3
31	LT235/75R15 <small>RWL</small>	104/101Q	6	733	235	6.5J	14.3
32	LT245/70R16 <small>RWL</small>	113/110Q	8	750	248	7.0J	14.3
33	LT245/75R16 <small>RWL</small>	120/116Q	10	774	248	7.0J	14.3
34	LT265/75R16 <small>RWL</small>	123/120Q	10	804	267	7.5J	14.7

PCR

UHP

HT

AT

MT

LTR

WINTER

VANMATE



NO	SIZE	L/ISS	PR	OD (mm)	SW (mm)	RIM	G.D					dB
1	195R14C	102/100R	8	652	189	5.5J	8.5	E	B			72
2	195/70R15C	104/102R	8	655	201	6.0J	8.5	E	B			72
3	205/65R15C	102/100T	6	647	209	6.0J	8.5	E	B			72
4	215/65R15C	104/102T	6	661	221	6.5J	8.5	E	B			72
5	225/70R15C	112/110R	8	697	228	6.5J	8.5	E	B			72
6	195/60R16C	99/97T	6	640	201	6.0J	8.5	E	B			72
7	195/65R16C	104/102R	8	660	201	6.0J	8.5	E	B			72
8	205/65R16C	107/105R	8	736	208	6.0J	8.5	E	B			72
9	205R16C	110/108R	8	672	209	6.0J	8.5	E	B			72
10	205/75R16C	110/108R	8	714	203	5.5J	8.5	E	B			72
11	215/60R16C	108/106T	8	664	221	6.5J	8.5	E	B			72
12	215/65R16C	109/107T	8	686	221	6.5J	8.5	E	B			72
13	215/76R16C	113/111R	8	728	216	6.0J	8.5	E	B			72
14	225/65R16C	112/110T	8	698	228	6.5J	8.5	E	B			72
15	235/65R16C	115/113R	8	712	240	7.0J	8.5	E	B			72

TRAVOMATE



Compact shoulder pattern enhance the shoulder stability,optimize high-speed cornering performance.
 Double steel belt efficiently improve tire wear resistance and uniformity.
 Reinforced shoulder rib pattern adapt to all season utilization.
 Specific recipe assure superior shearing resistance, puncture resistance and anticorrosive.

NO	SIZE	L/ISS	PR	OD (mm)	SW (mm)	RIM	G.D				dB
1	155R13C	85/83R	6	578	157	4.5J	8.0	TBD	TBD		71
2	88/86S	88/86R	6	562	170	5.0J	8.0	TBD	TBD		71
3	165R13C	91/89R	6	596	167	4.5J	8.0	TBD	TBD		71
4	175R14C	99/98Q	8	636	177	5.0J	8.5	E	B		71
5	175/65R14C	90/88T	6	584	177	5.0J	8.0	E	B		71
6	95/93S	95/93R	6	602	177	5.0J	8.0	TBD	TBD		71
7	185R14C	102/100R	8	652	189	5.5J	10.5	E	B		71
8	195R14C	106/104Q	8	668	196	5.5J	8.5	E	B		71
9	205/75R14C	109/107R	8	664	203	5.5J	8.5	E	B		71
10	195/70R15C	104/102S	8	655	201	6.0J	10.5	E	B		71
11	106/104R	106/104Q	8	693	196	5.5J	8.5	E	B		71
12	205/70R15C	106/104R	8	669	209	6.0J	10.5	E	B		71
13	205/75R15C	103/100R	8	689	203	5.5J	8.5	E	B		71
14	215/70R15C	109/107R	8	683	221	6.5J	8.5	E	B		71
15	225/70R15C	112/110R	8	697	228	6.5J	8.5	E	B		71
16	175/75R16C	101/99R	8	668	177	5.0J	8.0	E	B		71
17	185/75R16C	104/102R	8	684	184	5.0J	8.5	E	B		71
18	195/75R16C	107/105R	8	698	196	5.5J	8.5	E	B		71
19	215/70R16C	108/106R	8	709	221	6.5J	8.5	E	B		71
20	215/75R16C	113/111R	8	728	216	6.0J	9.0	E	B		71
21	102/100R RWW	102/100N	8	652	189	5.5J	10.5	E	B		71
22	195R14C RWW	106/104Q	8	668	196	5.5J	8.5	E	B		71
23	205/75R14C RWW	109/107R	8	664	203	5.5J	8.5	E	B		71
24	195R15C RWW	106/104R	8	693	196	5.5J	8.5	E	B		71
25	205/75R15C RWW	103/100R	8	689	203	5.5J	8.5	E	B		71

SNOWIDE



NO	SIZE	L/I&SS	OD (mm)	SW (mm)	RIM	G.D					dB
1	155/65R13	73T	532	157	4.5J	8.5	E	F			67
2	165/70R13	79T	562	170	5.0J	8.6	E	F			67
3	175/70R14	84S	602	177	5.0J	8.6	E	F			67
4	175/65R14	82T	584	177	5.0J	8.6	E	F			67
5	185/60R14	82T	578	189	5.5J	8.6	E	F			67
6	185/65R14	86T	596	189	5.5J	8.6	E	F			67
7	195/60R14	86H	590	201	6.0J	8.5	E	F			67
8	185/55R15	86H XL	585	194	6.0J	8.5	E	F			67
9	185/60R15	84H	603	189	5.5J	8.8	E	F			67
10	185/65R15	88T	621	189	5.5J	8.6	E	F			67
11	195/55R15	85V	595	201	6.0J	8.6	E	F			67
12	195/60R15	88T	615	201	6.0J	8.6	E	F			67
13	195/65R15	91T	635	201	6.0J	8.6	E	F			67
14	205/65R15	94H	647	209	6.0J	8.6	E	F			67
15	195/50R16	88H XL	602	201	6.0J	8.8	E	F			67
16	195/55R16	91H XL	620	201	6.0J	8.8	E	F			67
17	205/60R16	92T	652	209	6.0J	8.8	E	F			67
18	205/55R16	91T	632	214	6.5J	8.6	E	F			67
19	215/55R16	97V XL	642	226	7.0J	8.6	E	F			67
20	225/55R16	99H XL	654	233	7.0J	8.8	E	F			67
21	215/60R16	95H	664	221	6.5J	8.8	E	F			67
22	225/65R17	102T	724	228	6.5J	8.8	E	F			67
23	215/50R17	95V XL	648	226	7.0J	8.8	E	F			67
24	215/55R17	98V XL	668	226	7.0J	8.8	E	F			67
25	225/45R17	94V XL	634	225	7.5J	8.8	E	F			67
26	225/50R17	98V XL	658	233	7.0J	8.8	E	F			67
27	225/55R17	101V XL	680	233	7.0J	8.8	E	F			67
28	235/45R17	97V XL	644	236	8.0J	8.8	E	F			67
29	235/55R17	103VXL	690	245	7.5J	8.8	E	F			67
30	245/45R17	99V XL	652	243	8.0J	8.8	E	F			67
31	225/45R18	95V XL	659	225	7.5J	8.8	E	F			67
32	235/45R18	98V XL	669	236	8.0J	8.8	E	F			67
33	245/45R18	100V XL	677	243	8.0J	8.8	E	F			67
34	245/50R18	104V XL	703	253	7.5J	8.8	E	F			67
35	255/40R18	99V XL	661	260	9.0J	8.3	E	F			TEST
36	255/45R18	103V XL	687	255	8.5J	8.8	E	F			TBD
37	275/45R18	107V XL	705	273	9.0J	8.3	E	F			TEST
38	225/45R19	96V XL	685	225	7.5J	8.8	E	F			67
39	245/45R19	102V XL	703	243	8.0J	8.8	E	F			TBD



NO	SIZE	L/ISS	OD (mm)	SW (mm)	RIM	G.D				dB
1	215/75R15	100T	703	216	6.0J	9.6	E	E		73
2	235/75R15	109T XL	733	235	6.5J	9.6	E	E		73
3	215/65R16	96T	686	221	6.5J	9.6	E	E		73
4	215/70R16	100T	708	221	6.5J	9.6	E	E		73
5	235/60R16	100T	688	240	7.0J	9.6	E	E		73
6	235/70R16	106T	736	240	7.0J	9.6	E	E		73
7	215/60R17	96T	690	221	6.5J	9.6	E	E		73
8	225/60R17	99T	702	228	6.5J	9.6	E	E		73
9	225/65R17	102T	724	228	6.5J	9.6	E	E		73
10	235/65R17	104T	738	240	7.0J	9.6	E	E		73
11	265/65R17	112T	776	272	8.0J	9.6	E	E		73
12	215/55R18	95T	693	226	7.0J	9.6	E	E		73
13	225/55R18	98T	705	233	7.0J	9.6	E	E		73
14	235/50R18	97T	693	245	7.5J	9.6	E	E		73
15	235/55R18	100T	715	245	7.5J	9.6	E	E		73
16	235/60R18	107T XL	739	240	7.0J	9.6	E	E		73
17	245/60R18	105T	751	248	7.0J	9.6	E	E		73
18	255/55R18	109T XL	737	265	8.0J	9.6	E	E		73
19	225/55R19	99T	731	233	7.0J	9.6	E	E		73
20	235/50R19	103T XL	719	245	7.5J	9.6	E	E		73
21	235/55R19	105T XL	741	245	7.5J	9.6	E	E		73
22	245/55R19	103T	753	253	7.5J	9.6	E	E		73
23	255/45R19	104T XL	713	255	8.5J	9.6	E	E		73
24	255/50R19	107T XL	739	265	8.0J	9.6	E	E		73
25	245/45R20	103T XL	728	243	8.0J	9.6	E	E		73
26	255/45R20	105T XL	738	255	8.5J	9.6	E	E		73
27	255/55R20	110T XL	788	265	8.0J	9.6	E	E		73
28	275/45R20	110T XL	756	273	9.0J	9.0	E	E		73
29	275/50R20	113T XL	784	284	6.5J	9.0	E	E		73